

SAFETY DATA SHEET

Issuing Date: 28-Apr-2015 Revision Date: 30-Oct-2022 Revision Number: 4

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

SDS-108

Product Name

LT9X, LT9XH, LT9X55, LT9X55H, LT9X330, LT9X330H

Other means of identification

None

Recommended use of the chemical and restrictions on use

Recommended Use

Process fluid for honing machines. For industrial use only

Uses advised against

Do not use for grinding process

Suppliers Details

Supplier Address
Sunnen Products Company
7910 Manchester Rd.
Saint Louis, MO 63143
Website

www.sunnen.com

Email

SDS@Sunnen.com

Manufacturer Contact

Engineered Lubricants Co. 11525 Rock Island Ct. Maryland Heights, MO 63043

Emergency telephone number

CHEMTREC (800) 424-9300

24 hrs./Day 7 days/ week CCN 7766 (US&CA)

2. HAZARDS IDENTIFICATION

Classification

Not Classified according to 2012 OSHA HAZ COM Standard; 29 CFR Part 1910.1200

GHS Label elements, including precautionary statements

None

Emergency Overview

Precautionary Statements

Prevention

None

General Advice

None

Storage

None

Disposal

None

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Prolonged skin contact may defat the skin and produce dermatitis Prolonged or repeated skin contact can cause skin irritation or oil acne: Inflammation and blackheads due to mechanical blockage of the pores.

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
None			

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

INHALATION: Remove from further exposure. If unconsciousness occurs, seek immediate medical assistance, and call a physician. If breathing has stopped, begin mouth to mouth resuscitation.

EYE CONTACT: Remove contact lenses (if wearing) and flush eyes with water for 15 minutes. Seek medical attention to check for possible irritation.

SKIN CONTACT: Wash contact areas with mild non-abrasive soap and water.

INGESTION: Do not induce vomiting. Call physician or poison control center immediately.

Most Important Symptoms/Effects Acne, blackheads

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media water spray

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. Although not classified as "combustible" (based on flash point and ignition properties) this product can be made to burn and will serve as a fuel source for a fire. Sealed containers may melt, leak, burst or explode, releasing contents and spreading fire, if exposed to extreme heat. Towels, rags or other insulating absorbent fibrous media contaminated with honing oil should be stored in appropriate fireproof container that is emptied daily to avoid spontaneous combustion hazard. Remove traces of product if soldering, welding, brazing, cutting or other process involving ignition sources to prevent a fire hazard.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear appropriate protective clothing. Wash thoroughly after handling.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment

Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up

Dam up. Soak up with inert absorbent material. Clean up promptly by sweeping or vacuum. Towels, rags or other insulating absorbent fibrous media contaminated with honing oil should be stored in appropriate fireproof container that is emptied daily to avoid spontaneous combustion hazard.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Wear personal protective equipment. Use only in ventilated areas. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Avoid wearing clothing soaked with fluid. Remove and wash contaminated clothing before re-use.

Use according to package label instructions. Use only in Honing Machines. Mix only with other Sunnen Honing oils. Clean oil covered parts with alkaline cleaner. Contact with water or alkaline material can lead to formation of non-hazardous soaps which can clog the honing machines oil filter. If spilled, take caution, as material can cause surfaces to become very slippery.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed. Store locked up.

Incompatible Products Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Using proper engineering controls (local ventilation) normal honing operations should not generate mists at the operator's breathing zone. This product is considered a metalworking fluid (MWFs). Currently two OSHA air contaminant permissible exposure limits apply to MWFs. They are 5 mg/m³ for an 8-hr. time weighted average (TWA) for mineral oil mist and 15 mg/m³ (8hr. TWA) for Particulates Not Otherwise Classified (PNOC) [applicable to all other metalworking fluids].

The American Conference of Governmental Industrial Hygienists (ACGIH) threshold limit value (TLV) for mineral oil is 5 mg/m³ for an 8 hr. TWA and 10 mg/m³ for a 15 minute short term exposure limit (STEL).

In 1998, The National Institute for Occupational Safety and Health (NIOSH) published a criteria document which recommended an exposure level (REL) for MWF aerosols of 0.4 mg/m³ for thoracic particulate mass as a TWA concentration for 10 hours per day during a 40 hr. work week. Because of the limited availability of thoracic samplers, measurement of total particulate mass is an acceptable substitute. The thoracic particulate value corresponds to 0.5 mg/m³ for total particulate mass.

In 1999, the OSHA Metalworking Fluids Standards Advisory Committee recommended a new 8 hr. TWA PEL of 0.4 mg/m³ thoracic particulate (0.5 mg/m³ total particulate).

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
None			

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields. If splashes are likely to occur, wear: Goggles. **Skin and Body Protection** Skin protection is not normally required for short exposures when honing with oil. Oil

impervious gloves should be worn. Nitrile gloves are recommended.

Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Note some barrier creams have been shown to

increase skin absorption of metallic compounds.

Respiratory Protection In case of mist, spray or aerosol exposure wear suitable personal respiratory protection.

Handle in accordance with good industrial hygiene and safety practice. Provide regular **Hygiene Measures**

cleaning of equipment, work area and clothing. Wash hands thoroughly to remove honing oil and microscopic particles of metal debris. Do not consume or store food in the work area. Remove and wash contaminated clothing before re-use. Avoid contact with open cuts or

None known

None known

None known

sores.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State: Liquid

Odor: Oily

Appearance: Black Odor Threshold: Unknown

Values Remarks/Method Property No data available pН None known Melting Point/Range No data available None known **Boiling Point/Boiling Range** No data available None known Flash Point Closed cup: >177°C (350°F) None known **Evaporation rate** No data available None known

Flammability (solid, gas) Flammability Limits in Air

No data available None known upper flammability limit No data available lower flammability limit No data available **Vapor Pressure** No data available **Vapor Density** No data available **Specific Gravity** 0.96 Typical

Water Solubility None None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/water No data available None known **Autoignition Temperature** No data available None known None known

Decomposition Temperature No data available Viscosity >86 cSt @ 40C Typical Flammable Properties Not flammable

Explosive Properties No data available **Oxidizing Properties** No data available

Other information

VOC Content (%) No data available VOC (g/l) 4 Gm/L ASTME1868-10

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Keep away from open flames, hot surfaces, and sources of ignition. Avoid accumulation of contaminated towels, rags or other insulating absorbent fibrous media.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

Carbon oxides. Sulfur oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product InformationNo acute toxicity information is available for this product.

Inhalation None under normal use conditions

Eye Contact Oil mists containing small metal filings may cause mechanical irritation.

Skin ContactNon-irritating during normal use. Prolonged or repeated skin contact can cause skin irritation

or oil acne: Inflammation and blackheads due to mechanical blockage of the pores.

Ingestion None under normal use.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Acne, blackheads

Delayed and immediate effects and also chronic effects from short and long term exposure

SensitizationNo information available.Mutagenic EffectsNo information available.CarcinogenicityNo information available

Chemical Name	ACGIH	IARC	NTP	OSHA
None				

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Numerical measures of toxicity - Product

Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
None				

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Since emptied containers retain material residue, follow label warnings even after container

is emptied. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Thoroughly drain containers and offer for recycling. Do not attempt to clean container as residue is difficult to remove. Empty drums should be completely drained, properly closed and returned to a drum conditioner to be commercially cleaned. Do not re-

use empty containers.

14. TRANSPORT INFORMATION

DOTNot regulatedTDGNot regulatedMEXNot regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
None					

U.S. EPA Label Information

EPA Pesticide Registration Number: Not applicable

16. OTHER INFORMATION

NFPA

Health Hazard 0 Flammability 1 Instability 0 Physical and Chemical Hazards 0

<u>HMIS</u>

Health Hazard 0 Flammability 1 Physical Hazard 0 Personal Protection X

Prepared By: Sunnen Products Company

7910 Manchester Road Saint Louis, MO 63143 1-314-781-2100

NOTICE

THIS MATERIAL SAFETY DATA SHEET ("MSDS") IS SUPPLIED PURSUANT TO THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION'S HAZARD COMMUNICATION RULE (THE "RULE"), 29 CFR 1910.1200. THIS MSDS IS BEING FURNISHED TO THE IMMEDIATE PURCHASER OF THE MATERIAL TO WHICH IT REFERS WITHOUT REPRESENTATION OR WARRANTY AS TO THE COMPLETENESS OR ACCURACY OF ANY INFORMATION OR RECOMMENDATIONS CONTAINED HEREIN.

THIS MSDS IS OFFERED SOLELY TO COMPLY WITH THE RULE AND IS NOT INTENDED TO CREATE ANY LIABILITY OF ANY KIND ON THE PART OF SUNNEN PRODUCTS COMPANY ("SUNNEN"). IN NO EVENT WILL SUNNEN BE RESPONSIBLE FOR ANY DEATH, INJURY OR DAMAGE OF ANY NATURE WHATSOEVER RESULTING FROM THE USE OF, RELIANCE UPON, OR MISUSE OF THE MSDS. NO REPRESENTATIONS OR WARRANTIES, WHETHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER NATURE, ARE MADE HEREUNDER. THIS MSDS IS NOT INTENDED AS A RECOMMENDATION FOR USES WHICH INFRINGE VALID PATENTS OR EXTEND LICENSES UNDER VALID PATENTS.

THIS MSDS IS FURNISHED UPON THE EXPRESS CONDITION THAT ALL PERSONS RECEIVING IT WILL MAKE THEIR OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR PURPOSED PRIOR TO USE. RESPONSIBILITY FOR COMPLIANCE WITH APPLICABLE FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING DISSEMINATION OF THE MSDS AND SALE AND USE OF THE MATERIAL TO WHICH IT REFERS RESTS SOLELY UPON THE PURCHASER.

End of Safety Data Sheet